SINAN SE-100

EXIT Sign Thermoplastic Housing Self Powered LED Lamps



DESCRIPTION

The SE-100R (LED Red) and SE-100G (LED Green) are economical and energy saving Exit signs. The injection molded plastic housing has soft rounded corners for aesthetic appeal. The LED lamps provide a maximum of energy savings potential and the battery pack allows the unit to be Self Powered during power outages.

APPLICATION

Suitable for use in almost any commercial or light industrial application.

APPROVALS

UL924. UL listed for damp locations. Life Safety NFPA 101.

HOUSING

The housing is made of injection molded thermoplastic making it impact resistant and corrosion proof. UL94-5V rated.

MOUNTING

Easy snap fit canopy can be used for top or end mounting or knockouts can be used for surface mounting. Included second face allows the unit to be used as a single or double face exit sign. Snap fitting, replaceable chevrons for direction indication.

LAMPS

Long life Light Emitting Diode (LED) lamps provide the maximum in energy savings.

ELECTRICAL/BATTERY

- Dual voltage input 120/277 VAC, 60 Hz.
- Maintenance free, Sealed Nickel Cadmium battery provides a minimum 1 ½ hour emergency operation.
- Low voltage disconnect of the battery prevents deep discharge and maintains good battery life.
- Fully automatic, solid state charger.
- Test switch with LED charge indicator/AC voltage indicator.

Catalog Number	Emergency	Lamp Type	Input Power 120V	Input Power 277V	Weight (Lbs)	Volume (cu. ft.)	Pieces Per Skid	Pieces Per 20'	Pieces Per 40'
SE-100R	Self Powered	LED Red	3.0 W	3.0 W	2.9	0.24	294	2940	5880
SE-100R-AC	AC Only	LED Red	3.0 W	3.0 W	2.8	0.24	294	2940	5880
SE-100G	Self Powered	LED Green	2.8 W	2.8 W	2.9	0.24	294	2940	5880
SE-100G-AC	AC Only	LED Green	2.8 W	2.8 W	2.8	0.24	294	2940	5880

Sinan Electric Co., Ltd.

Specifications and Dimensions subject to change without notice.